



POLYTROPIC
• POOL HEATING SOLUTIONS •



MORPHEO

Performance and customization



A HIGH-PERFORMANCE FULL-INVERTER HEAT PUMP WITH A CUSTOMIZABLE FRONT PANEL
for a better integration within its environment.
A Polytropic exclusivity !

POLYCONNECT²⁰
• INSIDE •

4G
optional



FULL
INVERTER

HEATCOOL

3 YEARS
POLYTROPIC



REFRIGERANT
R32

Certified
noise levels
Independent testing laboratory



Technical specifications

MODELS	MORPHEO XXS	MORPHEO XS	MORPHEO S	MORPHEO S+
SCOP according to EN 17645	7,0	7,9	8,2	7,2
Classification according to EN 17645	A	A	A	A
Recommended pool size*	15-30 m ³	30-45 m ³	45-55 m ³	55-70 m ³
Air 26°C / Water 26°C / Humidity 80%				
Energy Output BOOST mode	6,5 kW	8,5 kW	10,2 kW	12,6 kW
COP BOOST mode	5,7	5,3	6,0	5,1
Energy Output SMART mode	6,5 ~ 3,6 kW	8,5 ~ 4,1kW	10,2 ~ 5,2 kW	12,6 ~ 6,9 kW
COP SMART mode	7,6 ~ 5,7	10,2 ~ 5,3	9,4 ~ 6,0	9,8 ~ 5,1
Energy Output ECO-Silence mode	3,6 kW	4,1 kW	5,2 kW	6,9 kW
COP ECO-Silence mode	7,6	10,2	9,4	9,8
Air 15°C / Water 26°C / Humidity 70%**				
Energy Output BOOST mode	5,0 kW	6,4 kW	7,7 kW	9,4 kW
COP BOOST mode	4,5	4,2	4,4	4,1
Energy Output SMART mode	5,0 ~ 2,8 kW	6,4 ~ 3,3 kW	7,7 ~ 4,2 kW	9,4 ~ 5,0 kW
COP SMART mode	6,1 ~ 4,5	6,2 ~ 4,2	6,4 ~ 4,4	6,7 ~ 4,1
Energy Output ECO-Silence mode	2,8 kW	3,3 kW	4,2 kW	5,0 kW
COP ECO-Silence mode	6,1	6,2	6,4	6,7
Air 7°C / Water 26°C / Humidity 90%				
Energy Output BOOST mode	4,2 kW	5,0 kW	6,1 kW	7,7 kW
COP BOOST mode	4,0	3,8	4,2	3,7
Noise level CTTM mini-maxi (at 10m) according to EN ISO 3741: 2010 **	24 ~ 26 dB(A)	24 ~ 28 dB(A)	28 ~ 31 dB(A)	28 ~ 32 dB(A)
Noise level min-max (at 10m) acc. to EN ISO 3744 : 2010	21 ~ 24 dB(A)	23 ~ 26 dB(A)	24 ~ 28 dB(A)	25 ~ 30 dB(A)
Temperature working range	-3°C -> +43°C			
Installation				
Hydraulic connexions	1,5"/50 mm			
Power	220-240 V / 1+~N / 50 Hz			
Circuit breaker and cable size (for 20 m)	C 10 A (3G 2,5 mm ²)	C 10 A (3G 2,5 mm ²)	C 10 A (3G 2,5 mm ²)	C 16 A (3G 2,5 mm ²)
Power Input Max (air 26°C)	1,2 kW	1,6 kW	1,8 kW	2,5 kW
Minimum water flow	2 m ³ /h	3 m ³ /h	3 m ³ /h	4 m ³ /h
Dimensions in mm (L x l x h)	860 x 348 x 610			
Weight net (gross)	35 kg (48 kg)		44 kg (53 kg)	

* May to September with cover.

** Tests carried out at an air temperature of 15°C, with a water inlet at 26°C and a water outlet at 28°C to define the water flow rate, heating capacity and consumption, in accordance with FPP recommendations.

*** Noise levels in BOOST and ECO mode at 10 m, certified by the independent laboratory Centre de Transfert de Technologie du Mans, in accordance with EN ISO 3741: 2010

An exclusive system

INNOVATION !

The Morpheo pool heat pump features an exclusive system for quick replacement of the front panel to create a customised look.

- + **DISCRETION** : for a better integration into the garden
- + **DESIGN** : an attractive, distinctive look
- + **CUSTOMISATION** : a heat pump with a 'made-to-measure' look



AS STANDARD :
DARK
ABS 70% recycled
matt black



OPTIONAL :
WOOD
FSC wood from
sustainably
managed forests
Untreated - to be
stained.



The DARK ABS front panel is fitted as standard, but the optional front panel is supplied assembled:



OPTIONAL :
CRISTAL
High-gloss
white metal
en option



Focus on Morpheo Up

BENEFITS

The advantages of horizontal and vertical blowing in the same model!

- + This compact machine makes it easy to fit into small gardens.
- + No need for a 3 or 4 m clearance in front of the machine
- + Thanks to its double wall, the machine is closed: no water or leaves get inside



In matt black ABS 70% recycled



The airflow and sound waves are directed towards the sky



Equipment benefits



SIMPLE AND INTUITIVE OPERATION

A LCD touch screen to program, display the temperature and set time slots.

3 operating modes: Heating, Cooling and Automatic (heating or cooling to maintain set temperature).



OPTIMAL PERFORMANCES

Optimal Twist : Titanium heat exchanger in a PVC housing, efficient and corrosion resistant.



2D Technology : inverter compressor, higher COP thanks to the Hz by Hz variable speed motor.



DC Brushless : variable speed fan motor ensures optimal performances.



Reverse-cycle defrosting



LOW NOISE LEVELS

Standard sound insulation and variable compressor and fan speeds ensure extremely low noise levels.



CONNECTED SOLUTION

PolyConnect inside : wifi module and 4G key included for remote control via smartphone and permanent supervision by the Technicenter.
4G optional



ENERGY EFFICIENCY

- Full-Inverter Technology,
- Low impact R32 refrigerant,
- Enhanced COP.



INTELLIGENT OPERATING MODE

PolySmart Control : The heat pump regulates its own power to adapt to the needs of your pool, depending on the water temperature and the ambient temperature.

ACCESSORIES INCLUDED: winter cover, 50 mm hydraulic connection kit, 4 «Silent block» anti-vibration pads, condensate drainage kit.



LCD touch screen

INTUITIVE CONTROL

- Easy-to-read digital display
- Simple, intuitive touch adjustment
- Online video tutorial for a quick start



POLYCONNECT_{2.0}



CONNECTED SOLUTION

Easily connect the heat pump by scanning the QR code, **control** it via the free app and **benefit from secure remote supervision** for preventive maintenance and remote diagnosis by Polytropic technicians.

